

9902 & 9903 Electrical Testers provide voltage, continuity with one compact tool. They will turn on automatically when you place the probe across a complete circuit. So you don't even have to turn them on or off.



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031

Safety Conformance

Complies with EN 61010-1 for use in CATIII 600V environments



Model 9902

Features

	9902	9903
Automatically select VAC, VDC or Continuity test	*	*
1999 counts LCD display	*	*
Automatically power on and off	*	*
High input impedance	1MΩ	400kΩ
Non-contact voltage detection	9902N	9903N
Low battery indication		*

Specifications

Function	9902	9903	Accuracy
Voltage AC	690V	600V	±(3.0%±3d)
Voltage DC	220V	600V	±(1.5%±2d)
Continuity Test	*	*	

Size(HxWxD): 9902/9902N : 135mm x 51.5mm x 38.5mm
9903/9903N : 215mm x 72mm x 36.7mm

Weight: 9902/9902N :182g 9903/9903N : 235g

Accessories: Test leads, 2 x "AA" batteries and clamshell.



Model 9903



DT-9133 Lamp Tester

Lamp Tester tests HID and fluorescent lamps and has live conductor sensing. This electrical lamp tester has a compact, rugged housing with carrying case (included).

Specifications

Live Conductor Indication	60-250VAC, 40-60Hz
Continuity Verification	0-5MΩ (test current: <7μA)
Lamp Tester Voltage	3kV/160kHz (test current:<200μA)
Measurement Category	CAT II 250V

Size(HxWxD):189mm x 26.5mm x 2.6mm
Weight: 60g

- Double molded plastic housing
- CAT III 1000V

Model 9030

Bright Flashlight



Features

	9011/9011B	9020/9120	9021/9121	9030/9130
Clear LED indication	*	*	*	*
1999 counts LCD display with analog bargraph	*	*	*	*
AC/DC Voltage detection	*	*	*	*
Polarity detection	*	*	*	*
Single-pole phase test			*	*
Continuity test			*	*
Rotary field indication			*	*
Low impedance test	*	*	*	*
Flashlight		*	*	*
Voltage function operates without battery	*	*	*	*
IP64	*	*	*	*
Overvoltage class CATIII 1000V/CATIV 600V		*	*	*
VAT self-test button		*/	*/	*/



EMC & LVD
EN: 61326
EN: 61010-1
EN: 61243
EN: 61010-3 (9030/9130)

- Bright Flashlight
- VAT self-test button



Model 9011



Model 9121

Model 9020



Specifications

	9011/9011B	9020/9120	9021/9121	9030/9130
Voltage range (AC/DC)	6,12,24,50,120,230,400V	12,24,36,50,120,230,400V	12,24,36,50,120,230,400V	12,24,36,50,120,230,400V
Tolerance	-30% to 0% of reading	-30% to 0% of reading	-30% to 0% of reading	±1.5%±3D
ACV Frequency range	0~60Hz	0~60Hz	0~60Hz	50/60Hz
Internal impedance	-	<200kΩ/-	<200kΩ/-	≤1MΩ/-

Size(HxWxD): 240mm x 78mm x 40mm
Weight: 237g

Accessories:

Two "AAA" batteries (9021/9030/9121), gift box with carrying case